

PX Combi 821 Spraying monitor



Use

Is used for all field sprayers, where the liquid is registered by a flowmeter. The monitor can also be used for slurry wagons in connection with a slurry flowmeter.

Functions

- Measures speed
- Partial area
- Dosing – flow
- Total flow
- Flow factor
- Metrical or US-unit of measurements
- Can be connected to radar

Installation

The monitor is installed in the cabin with the fittings included. Installation guidelines for magnets and sensors are included.

Technical specifications

Size:	180 x 60 x 30 mm
Weight:	250 gram
Display:	6 digits with backlight
Input:	3 inputs which are used for wheel sensor, area counter and flow pulses
Voltage:	12 – 24 V

Ordering number

- 001-0-8210 PX Combi 821 includes:
- 1 monitor
 - 1 mounting kit for monitor
 - 2 pcs. reed sensors with 5.0 m cable
 - 2 pcs. ferrit magnets (20 x Ø 4.3 x 10 mm)
 - 1 cable 3.0 m (2 x 0.75 mm)
 - 1 mounting kit for sensors/magnets

Flowmeter – must be ordered separately

Lykketronic can deliver special designed flowmeters. The flowmeters are delivered for different types of mounting e.g. hose, valves and high pressure-blocks.

Please see separate product sheets for flowmeters.

Guarantee

1 year guarantee from date of delivery.