

# PX Combi 831 Tramline monitor - with tank level control



## Use

The monitor is used on seed drill machines for speed measuring, area counting and for tramlines when sowing.

The monitor can be connected to a sensor for monitoring the seed level in the seed box.

## Functions

- Measures speed
- Partial and total area
- Built-in tramline control = 1:2 1:3 1:4 1:5 1:6 1:7 1:8 1:9
- Tramline control right and left
- Tank level control
- Built-in clock

## Installation

The monitor is mounted in the cabin on enclosed mounting fittings. Mounting guide for magnets and sensors included.

## Technical specifications

Size:	180 x 60 x 30 mm
Weight:	250 gram
Display:	6 digits with backlight
Input:	4 inputs which are used for wheel sensor, area sensor, control of tramline clutches right and left
Output:	1 output for tramlining
Capacity:	6 A
Voltage:	12 - 24 V

## Ordering number

001-0-8310 PX Combi 831 includes:

- 1 monitor
- 1 mounting kit for monitor
- 2 pcs. reed sensors with 5.0 m cable
- 2 pcs. ferrit magnets (20 x Ø 4.3 x 10 mm)
- 1 pcs. battery cable 3.0 m (2 x 0.75 mm)
- 1 mounting kit for sensors/magnets

## Must be ordered separately:

Sensor for level control w/2.0 m cable  
Ordering number 110-1-2000

## Tramline clutches

Lykketronic can deliver tramline clutches. Please inform us about name and model of the sowing machine.

## Guarantee

1 year guarantee from date of delivery.